## **Product datasheet**

Specifications





# AvatarOn, 2 switches, 16AX, 250V, 1 way, Dark Grey

E8332L1\_DG

#### Main

| Product Or Component Type | Switch                                                 |
|---------------------------|--------------------------------------------------------|
| Device Application        | Control                                                |
| Load Type                 | Incandescent lamp Resistive Fluorescent lamp Inductive |
| Colour Tint               | Dark grey                                              |
| Colour Tint               | Dark grey                                              |

### Complementary

| Device Presentation          | Complete product                                                                                                          |  |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------|--|
| Rated Current                | 16 AX at 250 V AC 50/60 Hz                                                                                                |  |
| Switch Function              | 1-pole 1-way                                                                                                              |  |
| Number Of Gangs              | 2 gangs                                                                                                                   |  |
| Number Of Rocker             | 2                                                                                                                         |  |
| Clamping Connection Capacity | 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s)                                                          |  |
|                              | 4 x 1.5 mm² for solid cable(s)<br>4 x 1.5 mm² for stranded cable(s)                                                       |  |
| Connections - Terminals      | Brass terminal                                                                                                            |  |
| Material                     | Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator |  |
| Device Mounting              | Flush<br>Surface                                                                                                          |  |
| Width                        | 86 mm                                                                                                                     |  |
| Height                       | 86 mm                                                                                                                     |  |
| Depth                        | 34.2 mm                                                                                                                   |  |

#### **Environment**

| Ip Degree Of Protection                          | IP20         |
|--------------------------------------------------|--------------|
| Maximum Ambient Air<br>Temperature For Operation | 45 °C        |
| Operating Altitude                               | 2000 m       |
| Relative Humidity                                | 095 %        |
| Environmental Characteristic                     | UV resistant |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Standards IEC 60669-1

BS EN 60669-1 SS 227-1 MS IEC 60669-1

## **Packing Units**

| Unit Type Of Package 1       | PCE    |
|------------------------------|--------|
| Number Of Units In Package 1 | 1      |
| Package 1 Height             | 4.5 cm |
| Package 1 Width              | 8.5 cm |
| Package 1 Length             | 8.5 cm |
| Package 1 Weight             | 93.0 a |



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>②</b> | Toxic Heavy Metal Free     |     |
| <b>9</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration                                                                         |
|--------------------------|-------------------------------------------------------------------------------------------|
| Eu Rohs Directive        | Compliant EU RoHS Declaration                                                             |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile                                                             |
| Circularity Profile      | No need of specific recycling operations                                                  |