



Main

| | |
|---------------------------|------------------|
| Range of product | ZENcelo |
| Product or component type | Telephone socket |
| Connector type | RJ11 |
| Number of gangs | 2 gangs |
| Cover frame colour tint | White |

Complementary

| | |
|--------------------------------|--|
| Device mounting | Surface Flush |
| Socket additional information | Shuttered |
| Communication network category | Voice: 3 |
| Rated current | 1.5 A |
| Fixing mode | By screws M4 x 25 mm |
| Fixing center | 60.3 mm |
| Material | Polycarbonate: housing |
| Contacts material | Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating |
| Contact resistance | 1 μ Ohm |
| Insulation resistance | \geq 200 mOhm |
| Dielectric strength | 1000 V for 60 s at 60 Hz |
| AWG gauge | AWG 26...AWG 22 (4 twisted pair cables) |
| Minimum return loss | 23 dB |
| Embedding depth | 22.2 mm |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 30.4 mm |

Environment

| | |
|---------------------------------------|-----------------|
| Environmental characteristic | No UV resistant |
| Ambient air temperature for operation | -5...35 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------|-----------------------------------|
| Relative humidity | 0...95 % |
| Standards | TIA/EIA-568-B.2-1 ASTMD4566-98 |
