



Main

Range	ZENcelo
Product or component type	Switch
Switch function	1-way
Device application	Control
Number of gangs	4 gangs

Complementary

Device mounting	Surface Flush
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
Rated current	20 A at 250 V AC 50/60 Hz
Local signalling	Mechanical indicator (amber)
Material	Grid plate: polycarbonate + GF 20 % Base: polycarbonate Cover: polycarbonate Surround: polycarbonate
Load type	Incandescent lamp Resistive Inductive Fluorescent lamp
Colour tint	silver bronze
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	31 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	SS 227-1 EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1