



Main

| | |
|---------------------------|-----------------------|
| Range | ZENcelo |
| Product or component type | Multi-services socket |
| Device application | Media device support |
| Colour tint | Silver bronze |

Complementary

| | |
|-------------------------|---|
| Rated current | 2 A at 12 V DC, tolerance +/- 10 % |
| Connections - terminals | Plug in |
| Material | Box: cold-rolled steel Plate: cold-rolled steel Surround: PC Cover: PC |
| Device mounting | Flush 47 mm |
| Mounting support | Mounting box |
| Mounting location | False wall |
| Fixing mode | By 4 screws |
| Height | 64 mm |
| Width | 87 mm |
| Length | 350 mm |
| Connector type | USB SUB-D 15 HDMI 3.5 mm jack RCA |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | 0...40 °C operating 0...60 °C storage |
| Relative humidity | 10...90 % (operating) 0...95 % (storage) |
| Operating altitude | 2000 m |
| Standards | CISPR 22 FCC part 15 class A |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 885 g |
| Package 1 Height | 6.44 cm |
| Package 1 width | 35.76 cm |
| Package 1 Length | 8.6 cm |