



### Main

Range	Vivace
Product or component type	Switch
Device short name	KB31
Device presentation	Complete mechanism
Additional switch application	Do not disturb and clean up room

### Complementary

Marking	Bell symbol
Switch function	1-way
Actuator	Rocker
Pilot light	Indicator
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	10 A at 250 V AC, inductive 10 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	pillar terminal
Terminal identifier	COM N L2 L1
Tightening torque	0.4 N.m
Clamping connection capacity	<= 1.5 mm <sup>2</sup>
Width	86 mm
Height	86 mm

## Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

## Packing Units

Package 1 Weight	77.500 g
------------------	----------