



### Main

|                           |                    |
|---------------------------|--------------------|
| Range                     | Vivace             |
| Device short name         | KB31               |
| Product or component type | Speed controller   |
| Device presentation       | Complete mechanism |
| Colour tint               | White              |

### Complementary

|                                |   |
|--------------------------------|---|
| Power range                    | Motor: 250 VA   |
| [Ue] rated operational voltage | 220...240 V AC  |
| Network frequency              | 50 Hz   |
| Number of gangs                | 1 gang  |
| Connections - terminals        | Pillar terminals  |
| Terminal identifier            | L<br>Load   |
| Tightening torque              | 0.4 N.m   |
| Clamping connection capacity   | 1.5 mm <sup>2</sup>   |
| Contacts material              | Brass and phosphor bronze   |
| Material                       | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Nylon: base |
| Device mounting                | Flush   |
| Mounting support               | Wall mounted  |
| Fixing mode                    | By screw M3.5   |
| Fixing center                  | 60.3 mm   |
| Width                          | 87 mm   |
| Height                         | 87 mm   |
| Projecting depth               | 8 mm  |
| Embedding depth                | 35 mm   |

### Environment

|                                       |            |
|---------------------------------------|------------|
| Ambient air temperature for operation | -5...40 °C |
|---------------------------------------|------------|

|                              |            |
|------------------------------|------------|
| Relative humidity            | 0...95 %   |
| Environmental characteristic | Indoor use |

### Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 93.000 g |
| Package 1 Height | 1.000 mm |
| Package 1 width  | 1.000 mm |
| Package 1 Length | 1.000 mm |