



### Main

Range	Vivace
Product or component type	USB charger
Fixing mode	Screw

### Complementary

Device mounting	Flush
Device presentation	Mechanism
Colour tint	White
Surface finish	Glossy
Surface treatment	Untreated
Number of modules	1 module 46 x 36.7 x 21.7 mm
Condition of use	Room temperature
Ambient air temperature for storage	-5...60 °C
Relative humidity	10...90 %
[Ue] rated operational voltage	100/240 V AC 50/60 Hz
Integrated connection type	1 USB port 5 V DC, maximum load current: 2.1 A
Material	Silicone rubber: cover PC (polycarbonate): grid plate PC (polycarbonate): housing
Shape of screw head	Cross
Number of terminals	2 screw terminals
Clamping connection capacity	2.5 mm <sup>2</sup> for stranded cable(s) 2.5 mm <sup>2</sup> for flexible cable(s) 2.5 mm <sup>2</sup> for rigid cable(s) 1.5 mm <sup>2</sup> for stranded cable(s) 1.5 mm <sup>2</sup> for flexible cable(s) 1.5 mm <sup>2</sup> for rigid cable(s)
Wire stripping length	6 mm
Product compatibility	HTC Samsung HW Apple XiaoMi Power bank

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

### Major smart phone and tablet

Height	87 mm
Width	87 mm
Depth	37.1 mm
Embedding depth	27.3 mm
Net weight	0.0712 kg

### Environment

Product certifications	CCC IEC
IP degree of protection	IP20
Environmental characteristic	Liquid soap Alcohol

### Packing Units

Package 1 Weight	72.000 g
Package 1 Height	86.000 mm
Package 1 width	35.000 mm
Package 1 Length	86.000 mm