

EasyPact TVS - auxiliary contact block - 2 NC - screw-clamps terminals

LAEN02

Main

| Range | Easy TeSys | |
|---------------------------|-------------------------|--|
| Range of product | Easy TeSys Control | |
| Product or component type | Auxiliary contact block | |
| Device application | Signalling | |
| Device short name | LAEN | |
| Colour | Grey (RAL 7011) | |

Complementary

| · · · · · · · · · · · · · · · · · · | | |
|---|---|--|
| Range compatibility | EasyPact EasyPact TVS LC1E | |
| Mounting location | Front | |
| Auxiliary contacts operation | Instantaneous | |
| Pole contact composition | 2 NC | |
| [Ui] rated insulation voltage | 690 V - for control circuit conforming to IEC 60947-5-1 | |
| [Ue] rated operational voltage | <= 690 V | |
| [Ith] conventional free air thermal current | 8 A (at 60 °C) | |
| Irms rated making capacity | 140 A AC conforming to IEC 60947-5-1 | |
| [lcw] rated short-time withstand current | 100 A - 1 s 120 A - 500 ms 140 A - 100 ms | |
| Protection type | GG fuse 10 A | |
| Mechanical durability | 10 Mcycles | |
| Minimum switching current | 5 mA | |
| minimum switching voltage | 17 V | |
| Non-overlap time | 1.5 ms on energisation no overlap between NC and NO contact 1.5 ms on de-energisation no overlap between NC and NO contact | |
| Insulation resistance | > 10 MOhm | |
| Connections - terminals | Control circuit: screw clamp terminals 1 1 mm² - external diameter: 6 mm - cable stiffness: solid or flexible with cable end Control circuit: screw clamp terminals 1 1 mm² - external diameter: 6 mm - cable stiffness: solid or flexible without cable end Control circuit: screw clamp terminals 2 2.5 mm² - external diameter: 6 mm - cable stiffness: solid or flexible with cable end Control circuit: screw clamp terminals 2 2.5 mm² - external diameter: 6 mm - cable stiffness: solid or flexible without cable end | |
| Net weight | 0.035 kg | |

Environment

| Environmental characteristic | Standard environment | |
|---------------------------------------|------------------------------|--|
| Standards | IEC 60947-5-1 | |
| Product certifications | GOST | |
| IP degree of protection | IP20 conforming to IEC 60529 | |
| Protective treatment | TH conforming to IEC 60068 | |
| Ambient air temperature for operation | -555 °C | |
| Ambient air temperature for storage | -6080 °C | |
| Operating altitude | 3000 m without derating | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|--------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.8 cm |
| Package 1 Width | 5 cm |
| Package 1 Length | 5.2 cm |
| Package 1 Weight | 34 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 100 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 3.8 kg |

Contractual warranty

Warranty 18 months

27-Mar-2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 4 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Packaging made with recycled cardboard | Yes |
|--|-------------------|
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACh Regulation | REACh Declaration |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |