

EvoPact HVX embedded pole, VCB withdrawable, 24kV, 25kA, 630A, 275mm

HVE242506E275F

Main

Range of product	EvoPacT
Device short name	HVX-EP
Product or component type	Circuit breaker
Variant	Equipped
Technology type	Vacuum
Rated frequency (fr)	50/60 Hz
Standards	IEC 62271-100
Rated voltage (Ur)	24 kV
Rated continuous current (Ir)	630 A
Phase distance	275 mm
Number of poles	3.0
Network type	AC
Control type	Push-button
Mounting mode	Withdrawable Fixed

Complementary

Rated operating sequence	O - 0.3 s - CO - 15 s - CO O - 3 min - CO - 3 min - CO O - 0.3 s - CO - 3 min - CO
Operating time	3060 ms opening < 60 ms breaking < 70 ms closing

Environment

Ambient air temperature for -25...40 °C operation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Take-back

ଞ Materials and Packaging		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
Jse Again		
○ Repack and remanufacture		

No