

# TeSys D control relay - 5 NO - <= 690 V - 220 V AC standard coil

CAD50M7

## Main

| TeSys<br>TeSys Deca |   |
|---------------------|---|
| TeSys CAD           |   |
| Control relay       |   |
| CAD                 |   |
| Control circuit     |   |
|                     |   |
|                     | TeSys Deca  TeSys CAD  Control relay  CAD |

| Utilisation category                        | AC-15   |  |
|---|---|--|
| 0 3   | AC-14   |  |
|   | DC-13   |  |
|   | 50-10   |  |
| Pole contact composition                    | 5 NO  |  |
| [Ue] rated operational voltage              | <= 690 V AC 25400 Hz  |  |
| Control circuit type                        | AC at 50/60 Hz  |  |
| [Uc] control circuit voltage                | 220 V AC 50/60 Hz   |  |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947  |  |
| [Ith] conventional free air thermal current | 10 A (at 60 °C)   |  |
| Irms rated making capacity                  | 140 A AC conforming to IEC 60947-5-1                                |  |
| 3 4 3                                       | 250 A DC conforming to IEC 60947-5-1                                |  |
|   |   |  |
| [lcw] rated short-time withstand            | 100 A - 1 s   |  |
| current                                     | 120 A - 500 ms  |  |
|   | 140 A - 100 ms  |  |
| Associated fuse rating                      | 10 A gG conforming to IEC 60947-5-1                                 |  |
| [Ui] rated insulation voltage               | 600 V UL certified  |  |
|   | 600 V CSA certified   |  |
|   | 690 V conforming to IEC 60947-5-1                                   |  |
| Mounting support                            | Plate   |  |
| g capport                                   | Rail  |  |
| Our and the second second                   |   |  |
| Connections - terminals                     | Screw clamp terminals 1 cable(s) 14 mm²flexible without cable end   |  |
|   | Screw clamp terminals 2 cable(s) 14 mm²flexible without cable end   |  |
|   | Screw clamp terminals 1 cable(s) 14 mm²flexible with cable end      |  |
|   | Screw clamp terminals 2 cable(s) 12.5 mm²flexible with cable end    |  |
|   | Screw clamp terminals 1 cable(s) 14 mm²solid without cable end      |  |
|   | Screw clamp terminals 2 cable(s) 14 mm²solid without cable end      |  |
| Tightening torque                           | 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2  |  |
|   | 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm   |  |
|   | 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |  |
|   | · · · · · · · · · · · · · · · · · · ·                               |  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Control circuit voltage limits        | 0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz<br>0.81.1 Uc (-4060 °C):operational AC 50 Hz<br>0.851.1 Uc (-4060 °C):operational AC 60 Hz<br>11.1 Uc (6070 °C):operational AC 50/60 Hz   |  |
|---------------------------------------|---|--|
| Operating time                        | 1222 ms coil energisation and NO closing 412 ms coil de-energisation and NO opening   |  |
| Mechanical durability                 | 30 Mcycles  |  |
| Maximum operating rate                | 180 cyc/mn  |  |
| Inrush power in VA                    | 70 VA 50 Hz (at 20 °C)  |  |
| Hold-in power consumption in VA       | 8 VA 50 Hz (at 20 °C)   |  |
| Minimum switching voltage             | 17 V  |  |
| Minimum switching current             | 5 mA  |  |
| Non-overlap time                      | 1.5 ms on energisation between NC and NO contact     1.5 ms on de-energisation between NC and NO contact  |  |
| Insulation resistance                 | > 10 MOhm   |  |
| Mechanical robustness                 | Shocks control relay open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks control relay closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations control relay open: 2 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations control relay closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 |  |
| Height                                | 77 mm   |  |
| Width                                 | 45 mm   |  |
| Depth                                 | 84 mm   |  |
| Net weight                            | 0.58 kg   |  |
| Environment                           |   |  |
| Standards                             | EN/IEC 60947-5-1<br>GB/T 14048.5<br>UL 60947-5-1<br>CSA C22.2 No 60947-5-1<br>JIS C8201-5-1   |  |
| Product certifications                | CB CCC UL CSA EAC CE UKCA   |  |
| IP degree of protection               | IP2X front face conforming to VDE 0106  |  |
| Protective treatment                  | TH conforming to IEC 60068  |  |
| Ambient air temperature for operation | -4060 °C<br>6070 °C with derating   |  |
| Ambient air temperature for storage   | -6080 °C  |  |
| Operating altitude                    | 03000 m   |  |
| Packing Units                         |   |  |
| Unit Type of Package 1                | PCE   |  |
| Number of Units in Package 1          | 1   |  |
| Package 1 Height                      | 5.500 cm  |  |
| Package 1 Width                       | 8.200 cm  |  |
| Package 1 Length                      | 9.500 cm  |  |

| Package 1 Weight             | 352.000 g |
|------------------------------|-----------|
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 20        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 7.359 kg  |

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint                             |                               |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 17                            |
| Environmental Disclosure                              | Product Environmental Profile |

## **Use Better**

| Packaging made with recycled cardboard | No                                   |
|--|--------------------------------------|
| Packaging without single use plastic   | No                                   |
| EU RoHS Directive                      | Compliant with Exemptions            |
| SCIP Number                            | B67ac941-f42f-4afd-894a-0b6f9cefde62 |
| REACh Regulation                       | REACh Declaration                    |

## **Use Again**

| ○ Repack and remanufacture |   |
|----------------------------|---|
| Circularity Profile        | End of Life Information   |
| Take-back                  | No  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |