

TeSys Deca Manual Starter and Protector, auxiliary contact block, 1 NO and 1 NC, top mount, screw clamp

GVAE11

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys	
_	TeSys Deca	
	100/0 2000	
Device short name	GVAE	
Product or Component Type	Auxiliary contact block	
Product Compatibility	GV2P	
	GV2RT	
	GV2ME	
	GV3L	
	GV2LE	
	GV3P	
	GV2L	
Mounting Location	Front side	
Pole contact composition	1 NO + 1 NC	
Quantity per Set	Set of 10	

Complementary

oompromentary		
[Ui] rated insulation voltage	300 V UL 508 300 V CSA C22.2 No 14 250 V IEC 60947-1	
[Ue] rated operational voltage	24240 V AC 2460 V DC	
[Ith] conventional free air thermal current	2.5 A	
Mechanical durability	100000 cycles	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A	
Rated operational power in VA	120 VA 110120 V AC-15 100000 cycles 120 VA 230240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles	
Rated operational power in W	15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles	
Tightening torque	12.4 lbf.in (1.4 N.m) screw clamp terminals	
Height	0.4 in (11 mm)	
Width	1.8 in (45 mm)	
Depth	1.1 in (29 mm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight 0.04 lb(US) (0.02 kg)

Environment

Environmental characteristic	Normal environment
Product Certifications	UKCA

Ordering and shipping details

Category	US10I1122367	
Discount Schedule	0111	
GTIN	3389110343434	
Returnability	Yes	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.47 in (1.200 cm)	
Package 1 Width	2.36 in (6.000 cm)	
Package 1 Length	2.76 in (7.000 cm)	
Package 1 Weight	0.600 oz (17.000 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	2.44 in (6.200 cm)	
Package 2 Width	4.72 in (12.000 cm)	
Package 2 Length	2.91 in (7.400 cm)	
Package 2 Weight	6.138 oz (174.000 g)	
Unit Type of Package 3	S02	
Number of Units in Package 3	220	
Package 3 Height	5.91 in (15.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	9.090 lb(US) (4.123 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

GVAE11