

TeSys Deca - auxiliary contact block - 2 NO

GVAN20

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys TeSys Deca	
Device short name	GVAN	
Product or Component Type	Auxiliary contact block	
Product Compatibility	GV2ME GV3P GV2RT GV2LE GV2L GV3L GV3L	
Mounting Location	Left side	
Pole contact composition	2 NO	

Complementary

o o in promontary		
[Ui] rated insulation voltage	600 V UL 508 690 V IEC 60947-1 600 V CSA C22.2 No 14	
[Ue] rated operational voltage	48690 V AC 24240 V DC	
[Ith] conventional free air thermal current	6 A	
Mechanical durability	100000 cycles	
Minimum switching current	5 mA	
Minimum switching voltage	voltage 17 V	
Protection type	GB2CB circuit breaker GG fuse 10 A	
Rated operational power in VA	300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230240 V AC-15 100000 cycles 850 VA 380415 V AC-15 100000 cycles	
Rated operational power in W	120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles	
Tightening torque	12.4 lbf.in (1.4 N.m) screw clamp terminals	
Height	3.5 in (89 mm)	
Width	0.4 in (9.3 mm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	2.6 in (66 mm)	
Net Weight	0.11 lb(US) (0.05 kg)	
color	Dark grey	

Environment

Environmental characteristic	Normal environment
Product Certifications	UKCA

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0111
GTIN	3389110343502
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.70 in (9.400 cm)	
Package 1 Width	3.86 in (9.800 cm)	
Package 1 Length	5.91 in (15.000 cm)	
Package 1 Weight	1.446 oz (41.000 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	3.74 in (9.500 cm)	
Package 2 Width	3.86 in (9.800 cm)	
Package 2 Length	5.91 in (15.000 cm)	
Package 2 Weight	16.261 oz (461.000 g)	
Unit Type of Package 3	S02	
Number of Units in Package 3	60	
Package 3 Height	5.91 in (15.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	6.724 lb(US) (3.050 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

GVAN20