# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Closed toroid for residual current protection SA - Ø 200 mm

50441

### Main

Range	VigiPacT	
Device short name	SA200	
Product or component type	Earth leakage current sensor	
Device application	Equipment monitoring and control	
Range compatibility	VigiPacT RH10M residual current protection relay	
	VigiPacT RH10P residual current protection relay	
	VigiPacT RH21M residual current protection relay	
	VigiPacT RH21P residual current protection relay	
	VigiPacT RH68M residual current protection relay	
	VigiPacT RH86M residual current protection relay	
	VigiPacT RH86P residual current protection relay	
	VigiPacT RH99M residual current protection relay	
	VigiPacT RH99P residual current protection relay	
	VigiPacT RH197M residual current protection relay	
	VigiPacT RH197P residual current protection relay	
	VigiPacT RHU residual current protection relay	
	VigiPacT RHUs residual current protection relay	
	VigiPacT RMH residual current protection relay	
current sensor type	A type closed toroid	
[le] rated operational current	400 A	

# Complementary

1/1000	
AC/DC	
45440 Hz	
85 kA for 0.5 s	
85 kA / 0.5 s conforming to IEC 60947-2	
1000 V	
IV	
12 kV	
Fixed (cables) Fixed (plain backplate) Fixed (profiled sheet metal) Fixed (slotted backplate)	
7.05 MJ	
Screw connection 0.22 mm²	
196 mm inner:	
100 mm for 2 cables : 185 mm² (maximum)	
1.32 kg	

Height	256 mm
Width	274 mm
Depth	46 mm

### **Environment**

IP degree of protection	Connectors: IP20 IP30	
Environmental characteristic	Exposure to damp heat not in service (2555 °C, RH 95 %): 28 cycles conforming to IEC 60068-2-30  Salt mist: Kb/2 conforming to IEC 60068-2-52  Exposure to damp heat in service: category C2: 48 hours conforming to IEC 60068-2-56	
Pollution degree	Level 3 conforming to IEC 60664-1	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-5585 °C	
Standards	IEC 60947-2	
Product certifications	CE	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	27.000 cm
Package 1 Length	28.400 cm
Package 1 Weight	1.100 kg
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	13.800 kg
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	50.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	67.864 kg

# **Contractual warranty**

Warranty 12 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	94
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
Recycled metal content at CR level	0
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins