

Star-Delta Timing Relay - 0.05s... 300s - 24V DC / 24...240V AC - 1C/ O

RE22R1QCMU

Main

Range of product	Harmony Timer Relays
Discrete output type	Relay
Product or component type	Modular timing relay
Device short name	RE22
Nominal output current	8 A

Complementary

Contacts type and composition	1 C/O timed contact, cadmium free	
Time delay type	Star-delta	
Time delay range	10100 s 330 s 0.11 s 0.33 s 0.050.5 s 110 s 30300 s	
Control type	Rotary knob Diagnostic button	
[Us] rated supply voltage	24 V DC 24240 V AC 50/60 Hz	
Release input voltage	<= 2.4 V	
Voltage range	0.851.1 Us	
Supply frequency	5060 Hz +/- 5 %	
Connections - terminals	Screw terminals, 1 x 0.51 x 3.3 mm² (AWG 20AWG 12) solid without cable end Screw terminals, 2 x 0.52 x 2.5 mm² (AWG 20AWG 14) solid without cable end Screw terminals, 1 x 0.21 x 2.5 mm² (AWG 24AWG 14) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm² (AWG 24AWG 16) flexible with cable end	
Tightening torque	0.61 N.m conforming to IEC 60947-1	
Housing material	Self-extinguishing	
Repeat accuracy	+/- 0.5 % conforming to IEC 61812-1	
Temperature drift	+/- 0.05 %/°C	
Voltage drift	+/- 0.2 %/V	
Setting accuracy of time delay	+/- 10 % of full scale at 25 °C conforming to IEC 61812-1	
Time delay type	Star-delta - Qc-Star-delta relay (1 CO output)	
Insulation resistance	100 MOhm at 500 V DC conforming to IEC 60664-1	
Recovery time	120 ms on de-energisation	
Immunity to microbreaks	10 ms	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Power consumption in VA	35 VA at 240 V AC	
Power consumption in W	0.6 W at 24 V DC	
Switching capacity in VA	2000 VA	
Minimum switching current	10 mA at 5 V DC	
Maximum switching current	8 A	
Maximum switching voltage	250 V AC	
Electrical durability	100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1	
Mechanical durability	10000000 cycles	
Rated impulse withstand voltage	5 kV for 1.250 μs conforming to IEC 60664-1	
Power on delay	100 ms	
Creepage distance	4 kV/3 conforming to IEC 60664-1	
Overvoltage category	III conforming to IEC 60664-1	
Safety reliability data	MTTFd = 285.3 years B10d = 270000	
Mounting position	Any position	
Mounting support	35 mm DIN rail conforming to IEC 60715	
Status LED	LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (fast flashing) for timing in progress and output relay de-energised LED yellow (slow flashing) for timing in progress and output relay energised	
Function available	Qc-Star-delta relay (1 CO output)-1 C/O	
Width	22.5 mm	
Net weight	0.08 kg	
Control type	With test button	
Number of functions	1	

Environment

Dielectric strength 2.5 kV for 1 mA/1 minute at 50 Hz between relay output and power su insulation conforming to IEC 61812-1	
Standards	UL 508 IEC 61812-1
Directives	2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive
Product certifications	GL CE CCC EAC UL CSA RCM
Ambient air temperature for operation	-2060 °C
Ambient air temperature for storage	-4070 °C
IP degree of protection	IP40 housing: conforming to IEC 60529 IP50 front face: conforming to IEC 60529 IP20 terminals: conforming to IEC 60529
Pollution degree	3 conforming to IEC 60664-1
Vibration resistance	20 m/s² (f= 10150 Hz) conforming to IEC 60068-2-6

Shock resistance	15 gn not operating for 11 ms conforming to IEC 60068-2-27 5 gn in operation for 11 ms conforming to IEC 60068-2-27
Relative humidity	95 % at 2555 °C
Electromagnetic compatibility	Fast transients immunity test - test level: 1 kV level 3 (capacitive connecting clip) conforming to IEC 61000-4-4 Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC 61000-4-5 Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5 Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m level 3 (80 MHz1 GHz) conforming to IEC 61000-4-3 Conducted RF disturbances - test level: 10 V level 3 (0.1580 MHz) conforming to IEC 61000-4-6 Fast transient bursts - test level: 2 kV level 3 (direct contact) conforming to IEC 61000-4-4 Immunity to microbreaks and voltage drops - test level: 30 % (500 ms) conforming to IEC 61000-4-11 Immunity to microbreaks and voltage drops - test level: 100 % (20 ms) conforming to IEC 61000-4-11

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	8.4 cm
Package 1 Length	9.5 cm
Package 1 Weight	90.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.14 kg
Unit Type of Package 3	P06
Number of Units in Package 3	640
Package 3 Height	80.0 cm
Package 3 Width	80.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	73.38 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint		
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	43	

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7bdc2711-0ad2-427c-8ece-532c5e9f09d7

Use Again


○ Repack and remanufacture		
Take-back	No	

Product datasheet

RE22R1QCMU

Dimensions Drawings

Dimensions




Product datasheet

RE22R1QCMU

Connections and Schema

Wiring Diagram



Technical Description

Function Qc: Star-Delta Relay (1 CO)

Description

On energisation of power supply, the output R initializes at its initial state such that energizes STAR CONTACTOR + MAIN CONTACTOR and the timing T starts (STAR connection time duration starts). At the end of the timing period T, the output R closes such that deenergizes STAR CONTACTOR and deenergizes the power supply causes t transition time starts. At the end of the transition time, the output R reverts to its initial state such that energizes DELTA CONTACTOR.

Function: 1 Output



t:50 ms


Legend


Relay de-energised
Relay energised
Output open
Output closed

U -	Supply
T -	Timing period
t -	Delay to switch ON Delta contact output
R1 -	Star-Delta contact output

Technical Illustration

Dimensions





Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony Timer Relay



Offer Marketing Illustration

Product benefits / Features



Image of product / Alternate images

Alternative









