

shunt trip release with OC contact, Acti9, iMX+OF, voltage release, 12...24 VAC

A9A26948

Main

range of product	Acti9	
Product or component type	Shunt trip release with OC contact	
Device short name	iMX+OF	
Signal contacts composition	1 C/O	
[In] rated current	AC-12 6 A at 12 V, AC 50 Hz	
	AC-12 6 A at 24 V, AC 50 Hz	
	DC-12 6 A at 12 V, DC	
	DC-12 6 A at 24 V, DC	
[Uc] control circuit voltage	1224 V AC 50/60 Hz	
	1224 V DC	
9 mm pitches	2	

Complementary

J		
Range compatibility	Acti9 iC60H RCBO Acti9 iC60H RCBO PoN Acti9 iC60H2 RCBO Acti9 iC60N RCBO Acti9 iKQE RCBO	
Local signalling	Action indicator	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top: YES	
Width	18 mm	
Colour	White	
Connections - terminals	Clamp terminal - 2 cable(s) 2.5 mm² - flexible with cable end Clamp terminal - 1 cable(s) 6 mm² - rigid Clamp terminal - 2 cable(s) 2.5 mm² - rigid Clamp terminal - 1 cable(s) 4 mm² - flexible	
Tightening torque	1 N.m	
Compatibility code	IMX+OF	

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1	
Tropicalisation	2 conforming to EN/IEC 60947-5-1	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-3570 °C	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient air temperature for -40...85 °C storage

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.7 cm
Package 1 Width	8 cm
Package 1 Length	9.5 cm
Package 1 Weight	82 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	8.5 cm
Package 2 Width	10 cm
Package 2 Length	26.5 cm
Package 2 Weight	713 g
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.898 kg

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	