

VECTOR LED FLOOD



INPUT ⚡
220-240V

CRI
70

Life
50000 h

IP
65

Features

- Ideal for landscape, facade and sign lighting applications.
- Swivel arm for precise angle adjustment.
- IP65 sealed to provide complete protection against dirt, bugs and moisture.
- The Garden Light is constructed with a Die-cast aluminum housing.
- Tempered shatter-resistant glass.
- Sleek appearance and maximum durability.
- Efficient LED Light source with integral power supply.
- Corrosion resistant Inground spike for ease in installation.

Applications

General flood lighting luminaire for

- Parking lots
- Open storage areas
- Building exteriors
- Court yards
- Sign board etc.

CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (lm) 3000K / 4000K / 6000K	DIMENSIONS (mm)
CLS-VFL-10W	10	220-240 VAC	>0.9	3000K / 4000K / 6000K	900 / 950 / 1000	133 X 115 X 36
CLS-VFL-50W	50				4500 / 4750 / 5000	245 X 210 X 36
CLS-VFL-100W	100				9000 / 9500 / 10000	355 X 290 X 47
CLS-VFL-200W	200				18000 / 19000 / 20000	423 X 352 X 60

