

# ALTECO COLOR SELECT



INPUT ⚡  
110-240V

CRI >  
80

Life  
50000 h

IP  
20

IP  
44

## Features

- New range of back lit LED panels providing uniform diffused lighting option with optimum efficiency.
- 3000K, 4000K, 6000K CCT with Pre-settable tri white selector switch.
- Dual power selector switch providing liberty to run the fixture at 2 different wattages.
- Extremely thin design with only 34mm height.
- Beam angle > 170°, with PMMA lens inside.
- Without LGP, no yellowing risk or failure with extended operating hours.
- Uniform and soft lighting.
- Suspension and recessed installation for option.
- High quality SMD2835 LED chip with life >50000hrs @L70.

## Applications

General Lighting of Office, Retail outlets, Healthcare facilities, Educational institutes and Industries.

CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (lm)	DIMENSIONS (mm)
CLS-ALCS-2x2-28W/40W	28 / 40	110-240 VAC	>0.9	3000K	2700 / 4000	595 X 595 X 33
				4000K	2800 / 4100	
				6000K	2900 / 4200	
CLS-ALCS-1x4-28W/40W	28 / 40	110-240 VAC	>0.9	3000K	2700 / 4000	295 X 1195 X 32
				4000K	2800 / 4100	
				6000K	2900 / 4200	

