


**LED LINEAR LIGHT
AUSTUBE SLIM**



BATTEN LIGHT

SURFACE

SUSPENDED

AC 220-240V

15°/24°/36°

CRI≥80

NON DIMMABLE

DIMMABLE upon request

PF≥0.9

IP20

RoHS

CE

LIFE 50000 HOURS

FEATURES

- It can achieve Linear DIY seamless connection.
- Extremely slim with 36mm width only.
- Switchable 3CCT.
- Light downwards or upwards for option.
- Reflector+Lens Version: UGR<16; 15° /24° /36° lens beam angle available.

APPLICATIONS

- General lighting luminaire for
- General office areas
 - Board rooms
 - Receptions / Counters
 - Retail outlets
 - Showrooms
 - Multi purpose halls

SPECIFICATIONS

CODE	WATTS (W)	CCT (K)	LUMENS (lm)* 3000K/4000K/6000K	DIMENSIONS (mm) A X B X C
AUSLIM-DS-28W	28	3000K / 4000K / 6000K	2670 / 2715 / 2750	1202.5 X 36 X 70.5
AUSLIM-DE-28W	28		3280 / 3320 / 3360	1202.5 X 36 X 70.5
AUSLIM-RS-28W	28		3400 / 3460 / 3500	1202.5 X 36 X 70.5

*Lumen output with ±10% tolerance.



DIMENSIONS

