

INDOOR / OUUTDOOR LIGHTS



FEATURES

- Pc optics with 5 different beam angle options to suit every lighting demand.
- · Die-cast Aluminum housing with tempered glass cover.
- · High efficiency certified LED chip and driver.
- · >150 lm/W lumen efficiency.
- · Stylish white powder coat finish.
- · Plug and play sensor for option.
- Five installation options, recessed, surface mount, large adaptor plate for retrofit applications, bracket mount and pipe mount.
- · IP65, IK08 Class I protection rating.

APPLICATIONS

- Industrial facilities / Production Halls
- · Warehouses
- · Petrol pumps and filling stations
- School and university
- Gymnasiums
- Municipal facilities like community centers recreation centers, exhibition halls
- Departmental stores and shopping malls.

SPECIFICATIONS

CODE	WATTS (W)	CCT (K)	LUMENS (Im)* 5000K	DIMENSIONS (mm) A X B X C
CANOPY-C1-80W	80		12000	325 X 351.6 X 77.5
CANOPY-C1-100W	100	4000K /	15000	325 X 351.6 X 77.5
CANOPY-C1-120W	120	5000K /	18000	400 X 400 X 79.1
CANOPY-C1-150W	150	5700K /	22500	400 X 400 X 79.1
CANOPY-C1-180W	180	6500K	27000	400 X 400 X 79.1
CANOPY-C1-200W	200		30000	400 X 400 X 79.1

^{*}Lumen output with ±10% tolerance.










DIMENSIONS



PHOTOMETRICS



2000K 3000K 4000K 5000K 6000K 7000K 8000K 9000K 10000K