

ECO FLOOD LED FLOOD LIGHT



Features

- Black powder coated die cast Aluminum housing.
- Tempered front glass lens.
- High quality SMD 5730 LED chip.
- Upto 100lm/W lumen efficiency.
- More than 100° beam angle for maximum area coverage.
- Ra Index >70.
- Constant current integral LED driver with upto 5kV surge protection.
- Input voltage 220-240Vac with tolerance range of AC 100-265V.
- Protection rating: Class I, IP65, IK08.
- Temperature range: -40°C to 50°C.

Applications

- General areas lighting of
- Open yards
 - Recreational sports facilities
 - Small to medium scale industries
 - Warehouses
 - Building faculties

CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (lm) 3000K / 4000K / 6000K	DIMENSIONS (mm)
LED-ECOFL-10W	10	220 -240 VAC	>0.9	3000K / 4000K / 6000K	900 / 950 / 1000	133 X 115 X 36
LED-ECOFL-50W	50				4500 / 4750 / 5000	245 X 210 X 36
LED-ECOFL-100W	100				9000 / 9500 / 10000	355 X 290 X 47
LED-ECOFL-200W	200				18000 / 19000 / 20000	423 X 352 X 60

Dimensions / Weight

