



HIGHBAY LIGHT
ELEVA ECO G3



HIGHBAY LIGHT

SUSPENDED

AC
100-240V

60°/
90°/120°

CRI≥80

NON
DIMMABLE

PF≥0.9

IP65

IK08

RoHS

CE

LIFE
50000
HOURS

FEATURES

- ADC 12 Die-cast Aluminum housing with PC lens
- Highly efficient >185lm/W LED chip
- 6KV Surge Protection
- Powder coated external finish
- IP65 & IK08 double protection.
- Input voltage 100-240VAC, 50/60 Hz.
- Loop hanging / ceiling mounted options.
- 90° symmetric beam angle.
- Operating temperature -30° to 45°C.
- Certified LED chip and driver ensuring reliable performance.

APPLICATIONS

- Industrial facilities
- Manufacturing facilities
- Metallurgical industries
- Textile Industries
- Refineries
- Tanneries
- Warehouses
- School and university
- Gymnasiums
- Municipal facilities like community centers recreation centers, exhibition halls
- Departmental stores and shopping malls.



SPECIFICATIONS

CODE	WATTS (W)	CCT (K)	LUMENS (lm)* 6500K	DIMENSIONS (mm) A X B
ELEVA-ECOG3-100W	100	6500K	18500	Ø240 X 141
ELEVA-ECOG3-150W	150		27750	Ø280 X 149

*Lumen output with ±10% tolerance.



DIMENSIONS



ACCESSORIES



Bracket



Hook



Adaptor of pendant



PC reflector



Al reflector



Bottom cover of pc reflector



Water proof connector



Safety cord

