













OPTIMUS ECO LED LINKABLE LINEAR

Features

- Modular linear LED Lighting System is a consisting of trunking rails, luminaire inserts and accessories.
- Steel trunking housing
- Push and click LED modules and blank plate options.
- Pre wired 2.5mm² cable(1.5mm² for dimmers).
- Slide in lock design for interconnecting trunking segments.
- PMMA optical lens with 6 beam angle options.
- PMMA opal diffuser for 120° wide beam optics.
- SMD2835 LED chip with SDCM<4, Ra>80.
- Protection rating IP20, IP54 available upon request.
- 5/8/11 cables trunking modules to meet specific project requirements.

Applications

- High lumen output, 150lm/W standard, 160lm/W available upon request.

Applications

- The perfect continuous LED linear solution for industry, commercial and other applications.
- Perfect alternative of conventional linear fluorescent systems.

CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (lm) @4000K	DIMENSIONS (mm)
P03A-25W	25	220-240 VAC	>0.9	3000K / 4000K / 5000K	4000	1437 X 65 X 45
P03A-30W	30				4800	1437 X 65 X 45
P03A-35W	35				5600	1437 X 65 X 45
P03A-40W	40				6400	1437 X 65 X 45
P03A-45W	45				7200	1437 X 65 X 45
P03A-55W	55				8800	1437 X 65 X 45
P03A-65W	65				10400	1437 X 65 X 45
P03A-75W	75				12000	1437 X 65 X 45

Dimensions



Installation

