

PWFH WEATHER PROOF LED BATTEN



Features


- Adverse location weatherproof luminaire ideal for hostile and rugged environment. Completely dust and moisture proof offering wide range of applications with budget friendly conventional fluorescent as well as energy efficient LED lamp options to suite demand of every specific need.
- UV Stabilized Polycarbonate housing with impact resistant PMMA diffuser
- Stainless steel clips (Polycarbonate clips available on request)
- White powder coated gear tray suspend on lanyards for ease of maintenance.
- Silicon gasket
- 13.5 PG cable gland
- IP65 Protection from all sides.
- Compatible with conventional as well as LED T8 Tubes.

Applications

- Car parks
- Corridors
- Stairways
- Court yards
- Pool sides
- Washing bays
- Light to medium level Industrial installations

CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (Im) @4000K	DIMENSIONS (mm)
PWFH-118T8	1X18 LED T8	220 -240 VAC	>0.9	4000К (3000К / 5000К / 6500К optional)	1800	1265 X 100 X 62
PWFH-218T8	2X18 LED T8				3600	1265 X 135 X 62
PWFH-114T8	1X14 LED T8				2250	1265 X 100 X 62
PWFH-214T8	2X14 LED T8				4500	1265 X 135 X 62

Dimensions



FITTING	А	В	С
1x18W T8	1265	100	62
2x18W T8	1265	135	62
1x14W T8	1265	100	62
2x14W T8	1265	135	62

Photometrics

