



QUADRO LED



Features

- Powder coated Aluminum housing.
- Driver: Built-in
- Excellent heatsink design
- LED chips: COB
- Anti-glare reflector and diffuser designs
- Quality light with no noise, flickering, IR, or UV radiation
- High color rendering index (Ra≥80)
- Color Temperature: 3000K, 4000K, 5000K and 5700K
- Beam angle: 24° / 36° / 60°
- Protection rating IP54/ class I.
- Operating temperature -20°C to 45°C.
- Operating humidity 0-90%.

Applications

Residential, apartments, foyers, retail spaces, hotels, cafes and bars. Ideal for semi external areas like stair case awnings, pool sides, roof gardens etc.

CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (lm)	DIMENSIONS (mm)
					3000K / 4000K / 5000K / 5700K	
QUADRO-10W	10	220 -240 VAC	>0.9	3000K / 4000K / 5000K / 5700K	850 / 890 / 930 / 970	Ø90 X 100
QUADRO-15W	15				1275 / 1300 / 1390 / 1450	Ø90 X 100
QUADRO-25W	25				2120 / 2420 / 2320 / 2420	Ø120 X 110
QUADRO-35W	35				2970 / 3110 / 3255 / 3390	Ø160 X 120

Dimensions

