COARTS®
Lighting Solutions

LED BATTEN LIGHT
ECO BATTEN

LED

BATTEN LIGHT	SURFACE	AC 220-240V	120°	CRI≥70	NON DIMMABLE
PF≥0.9	IP20	RoHS	CE		LIFE 50000 HOURS

FEATURES

- Powder coated Aluminum body with PC diffuser. Stainless steel mounting clips.
- High efficiency SMD 2835 LED chip.
- Built in flicker free LED driver for suitable operation
- Shock resistant
- Compact and light weight design.
- RoHS complied. No hazardous material inside.
- Low maintenance cost

APPLICATIONS

General lighting luminaire for

- Showrooms
- Exhibition halls
- Retail Outlets
- Super Markets
- Offices
- Corridors
- Foyers etc.

SPECIFICATIONS

CODE	WATTS (W)	CCT (K)	LUMENS (lm)* 3000K / 4000K/6500K	DIMENSIONS (mm) A X B X C
CLS-ECOBTN-40W	40	3000K / 4000K / 6500K	3900 / 4000 / 4100	1188 X 59 X 29

*Lumen output with ±10% tolerance.

DIMENSIONS

A
B
C

PHOTOMETRICS

| 1000K | 2000K | 3000K | 4000K | 5000K | 6000K | 7000K | 8000K | 9000K | 10000K |