

FEATURES

- Die cast aluminum housing with tempered glass anti glare front lens.
- High efficient T-shape heat sink
- Faceted aluminum reflector for maximum light transmittance.
- High quality spring fixing mechanism suitable for installation in all types of false ceilings.
- Flicker free external driver with Triac, Analog and Dali dimming options.
- Certified COB chip and driver.
- 36°/60° beam angle options with 30° tiltable optics
- External LED driver with various control options.
- Fully protected IP 65 housing from below making it a suitable choice for damp environment.

APPLICATIONS


- Small compact fully enclosed adjustable downlight for
- Kitchen
 - Washrooms
 - Patio
 - Staircase
 - Pool sides
 - Health care facilities
 - Lobbies
 - Foyers

SPECIFICATION

CODE	WATTS (W)	CCT (K)	LUMENS (lm) 3000K/4000K/5000K	DIMENSIONS (mm) A X B	CUTOUT (mm)
FOCUS-5W	5		520 / 550 / 580	Ø80 X 30	Ø68-75
FOCUS-8W	8	2700K / 3000K /	830 / 880 / 910	Ø80 X 30	Ø68-75
FOCUS-10W	10	4000K / 5000K	1020 / 1100 / 1190	Ø110 X 49.5	Ø90-95
FOCUS-13W	13		1340 / 1430 / 1510	Ø110 X 49.5	Ø90-95



DIMENSIONS



PHOTOMETRICS

