

DS-7104HQHI-K1 Datasheet

[Get a Quote](#)

Overview

4 channels and 1 HDD mini size DVR
Efficient H.265 pro+ compression technology
Encoding ability up to 1080p @ 15 fps
5 signals input adaptively (HDTV/HD/CVI/CVBS/IP)
Up to 6 network cameras can be connected

Specification

DS-7104HQHI-K1 Specification	
Recording	
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding resolution	When 1080p Lite mode is not enabled: ,4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF;When 1080p Lite mode is enabled: ,4 MP lite/3 MP/1080p lite/720p lite/VGA/WD1/4CIF/CIF
Frame rate	Main stream:;When 1080p Lite mode not enabled: ,For 4 MP stream access:;4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) ,For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps;For 1080p stream access: ,1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N);For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N);When 1080p Lite mode enabled: ,4 MP lite/3 MP@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps ,(P)/30fps (N);Sub-stream: ,WD1/4CIF@12fps; CIF@25fps (P)/30fps (N);
Video bit rate	32 Kbps to 6 Mbps
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
Video And Audio	
IP video input	2-ch (up to 6-ch) Up to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog video input	4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	Support
Audio input	1-ch, RCA (2.0 Vp-p, 1 K Ω)
Audio output	1-ch, RCA (Linear, 1 K Ω)
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 K Ω) (using the first audio input)
Synchronous playback	4-ch

HDTVI input	4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60,*: The 3 MP signal input is only available for channel 1 of DS-7104HQHI-K1, channel 1/2 of DS-7108HQHI-K1, and channel 1/2/3/4 of DS-7116HQHI-K1.
VGA/HDMI output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Network	
Remote connections	32
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 6 TB capacity for each disk
Alarm in/out	N/A
USB interface	Real panel: 2 × USB 2.0
General	
Power supply	12 VDC
Consumption (without HDD)	≤ 8 W
Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
Weights (without HDD)	≤ 1 kg (2.2 lb)

Want to Buy

- Order Now
- Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+
Countries we Sold



18,000+
Customers Trusted



\$20,000,000
Inventory Available



50%-98%
Off Global List Price



100%
Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)

● Email: sales@router-switch.com