

DS-7204HUHI-K1/E Datasheet

Get a Quote



Overview

4 channels and 1 HDD 260 case DVR
Efficient H.265 pro+ compression technology
Encoding ability up to 8 MP lite @ 15 fps, 5 MP @ 12 fps
5 signals input adaptively (HDTV/ AHD/ CVI/ CVBS/ IP)
Up to 8 network cameras can be connected.

Specification

DS-7204HUHI-K1/E Specification	
Recording	
Encoding resolution	Main stream: When 8 MP Lite mode is not enabled: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) *: 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1/E. When 8 MP Lite mode enabled: 8 MP Lite/3MP/1080P/720P/WD1/4CIF/VGA/CIF@15 fps *: 8 MP Lite is only available for DS-7204HUHI-K1/E. Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)
Video bit rate	32 Kbps to 10 Mbps
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
Video And Audio	
Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Synchronous playback	4-ch
IP video input	4-ch (up to 8-ch);Up to 8 MP resolution;Support H.265+/H.265/H.264+/H.264 IP cameras
HDTV/ input	8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
HDCVI input	5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30
CVBS input	PAL/NTSC
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
Analog video input	4-ch;BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
AHD input	5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30
CVBS output	N/A

HDMI/VGA output	HDMI:1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI and VGA simultaneous output VGA:1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Network	
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Remote connections	32
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
Auxiliary Interface	
Capacity	Up to 10 TB capacity for each disk
Serial interface	N/A
USB interface	2 × USB 2.0
Alarm in/out	N/A
SATA	1 SATA interface
General	
Consumption(without HDD)	≤ 6 W
Working humidity	10% to 90%
Power supply	12 VDC
Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Dimensions(W × D × H)	265 × 225 × 48 mm (10.4 × 8.9 × 1.9 inch)
Weights (without HDD)	≤ 1.6 kg (3.5 lb)

Want to Buy

- Order Now
- Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+
Countries we Sold



18,000+
Customers Trusted



\$20,000,000
Inventory Available



50%-98%
Off Global List Price



100%
Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)

● Email: sales@router-switch.com