

# DS-7208HUHI-K1/E Datasheet

Get a Quote



## Overview

8 channels and 1 HDD 260 case DVR  
Efficient H.265 pro+ compression technology  
Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps  
5 signals input adaptively (HDTV/1/4CIF/CIF/1080P/720P)  
Up to 16 network cameras can be connected.

## Specification

### DS-7208HUHI-K1/E Specification

#### Recording

**Encoding resolution** Main stream: When 8 MP Lite mode is not enabled: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) \*: 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1/E. When 8 MP Lite mode enabled: 8 MP Lite/3MP/1080P/720P/WD1/4CIF/VGA/CIF@15 fps \*: 8 MP Lite is only available for DS-7204HUHI-K1/E. Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)

**Video bit rate** 32 Kbps to 10 Mbps

**Video compression** H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

**Dual stream** Support

**Stream type** Video, Video & Audio

**Audio compression** G.711u

**Audio bit rate** 64 Kbps

#### Video And Audio

**Audio input** 1-ch, RCA (2.0 Vp-p, 1 K $\Omega$ )

**Audio output** 1-ch, RCA (Linear, 1 K $\Omega$ )

**Synchronous playback** 8-ch

**IP video input** 8-ch (up to 16-ch);Up to 8 MP resolution;Support H.265+/H.265/H.264+/H.264 IP cameras

**HDTV input** 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25

**HDCVI input** 5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30

**CVBS input** PAL/NTSC

**Two-way audio** 1-ch, RCA (2.0 Vp-p, 1 K $\Omega$ ) (using the first audio input)

**Analog video input** 8-ch;BNC interface (1.0 Vp-p, 75  $\Omega$ ), supporting coaxitron connection

**AHD input** 5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30

**CVBS output** N/A

|                          |                                                                                                                                                                                                                                              |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HDMI/VGA output          | HDMI:1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI and VGA simultaneous outputVGA:1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz |
| Network                  |                                                                                                                                                                                                                                              |
| Network protocols        | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF                                                                                                                                                      |
| Remote connections       | 64                                                                                                                                                                                                                                           |
| Network interface        | 1, RJ45 10M/100M self-adaptive Ethernet interface                                                                                                                                                                                            |
| Auxiliary Interface      |                                                                                                                                                                                                                                              |
| Capacity                 | Up to 10 TB capacity for each disk                                                                                                                                                                                                           |
| Serial interface         | N/A                                                                                                                                                                                                                                          |
| USB interface            | 2 × USB 2.0                                                                                                                                                                                                                                  |
| Alarm in/out             | N/A                                                                                                                                                                                                                                          |
| SATA                     | 1 SATA interface                                                                                                                                                                                                                             |
| General                  |                                                                                                                                                                                                                                              |
| Consumption(without HDD) | ≤ 8 W                                                                                                                                                                                                                                        |
| Working humidity         | 10% to 90%                                                                                                                                                                                                                                   |
| Power supply             | 12 VDC                                                                                                                                                                                                                                       |
| Working temperature      | -10 °C to +55 °C (+14 °F to +131 °F)                                                                                                                                                                                                         |
| Dimensions(W × D × H)    | 265 × 225 × 48 mm (10.4 × 8.9 × 1.9 inch)                                                                                                                                                                                                    |
| Weights (without HDD)    | ≤ 1.6 kg (3.5 lb)                                                                                                                                                                                                                            |

## Want to Buy

- Order Now
- Get a Quote

## Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)

● Email: [sales@router-switch.com](mailto:sales@router-switch.com)