



DS-7716NI-K4/16P

NVR 16xIP@8MP 16xPoE 4xSATA 160Mbps



HIKVISION

- Number of IP channels : 16
- Optional discs : 4x SATA 6Gbps
- POE Interface : 16 x POE 100Mbps
- Analyzes : depending on the HIKVision camera
- Alarm Input : 16

VIDEO AUDIO INPUT

Number of IP channels	16
Two Way Audio Input	1-ch, RCA (2.0Vp-p , 1kohm)
IP Video Input Maximum Resolution	8MP (4K)
Video Input Technology	IP
Total video channels	16

NETWORK

Incoming Bandwidth	160
Outgoing Bandwidth	160
Remote connection	128
Web Browser Access	Firefox, Internet Explorer, Safari, Without plugin
Multi-streaming	2
Network Security	Password protection
DDNS	DynDNS, HI-DDNS
Total LAN ports	17
Number of PoE ports	16

AUDIO VIDEO OUTPUT

Monitor resolution	1080p, 4K
HDMI Output	1
VGA Output	1
Audio Output	1-ch, RCA (2.0Vp-p , 1Kohm)
CVBS output	None
Video Output for 4K	1x HDMI 1.4b
LCD monitor	No

DECODING

Decoding capability	16 MPixels, 16 simultaneous channels
---------------------	--------------------------------------

HARD DISK

Optional discs	4x SATA 6Gbps
HD Capacity	6TB Per HDD
Integrated drive	Without
External storage	NAS
redundant recording	Yes

EXTERNAL INTERFACE

Network Interface	16 x RJ-45 10/100 Mbps Ethernet, 1x RJ-45 100/1000 Mbps Ethernet
USB Interface	1 x USB Rear Pannel, 2 x USB Front Pannel
Alarm Input	16
Alarm output	4
Serial interface	RS232, RS485
RS Communication Protocol	HIKVISION-C, PELCO-D, Pelco P

SPECIFICATIONS

Power consumption (W)	20
Power supply	100 - 240VAC
Signal System	HDMI, HDMI 4K, IP, VGA

ENVIRONMENTAL

Working Temperature (°C)	From -10 to 55
Max. Working Humidity [%]	90
Weight (kg)	6.49
Chassis	19-inch Rack-mount 1.5U
Redundant Power Supply	No
19" Rack mounting	Yes
Included in the package	Brackets 19 ", Mouse, Quick Guide
Package volume (m3)	0.0393
Dimensions (H x W x D) [mm]	70 x 445 x 390

POE

POE Interface	16 x POE 100Mbps
POE Power	200
POE Interface Standard	802.3 af, Class 3, <15.4W, 802.3 at, Class 4, PoE+, <34W

BUILT IN FUNCTIONS

Analyzes	depending on the HIKVision camera
E-Mail	Events, system error
Calendar	Daily, Holidays, Working days
Video analysis in reading	Line crossing, Zone penetration

CERTIFICATIONS

Video resolution	4K, Full HD, HD
------------------	-----------------

FEATURES

Product description	• HDMI, VGA and CCTV video output are independent • All video outputs can display multi-windows
---------------------	---

WIFI

WiFi	No
------	----

CAMERA

Video Compression	H.264, H.264+, H.265, H.265+
-------------------	------------------------------

Accessories for DS-7716NI-K4/16P



WD10PURZ

HD 1TB, Maximum 64 Videostream



WD60PURZ

HD 6TB, Maximum 64 Videostream



WD20PURZ

HD 2TB, Maximum 64 Videostream



WD80PURZ

HD 8TB, Maximum 64 Videostream



WD30PURZ

HD 3TB, Maximum 64 Videostream



19" 1.5U Mounting
Bracket

1.5U 19" rack mount bracket



WD40PURZ

HD 4TB, Maximum 64 Videostream



WD82PURZ

HD 8TB, Maximum 64 Videostream



Distribution d'Équipement et de Matériel d'Alarme DEMA SA

CHEMIN DE LA VENDÉE 27

CH-1213 Petit-Lancy
t+41 22 879 69 00
f +41 22 879 69 10
@info@dema.ch

ALTE STEINHAUSERSTR. 19

CH-6330 Cham
t+41 41 740 69 00
f +41 41 740 69 03
@info@dema.ch