

DS-7716NI-K4 Datasheet

Check its price: [Click Here](#)

Overview

Hikvision DS-7716NI-K4 is the Embedded 4K NVR.

Quick Spec

Table 1 shows the quick spec.

Model	DS-7716NI-K4
Video/Audio input	IP video input: 16-ch Two-way audio: 1-ch, RCA (2.0 Vp-p, 1kΩ)
Network	Incoming bandwidth: 160 Mbps Outgoing bandwidth: 160 Mbps Remote connection: 128
Video/Audio output	Recording resolution: 8MP / 6MP / 5MP / 4MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF HDMI output resolution: 1-ch, resolution: 4K (3840*2160)/60Hz, 4K (3840*2160)/30Hz, 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz VGA output resolution: 1-ch, resolution: 1920*1080P/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz Audio output: 1-ch, RCA (Linear, 1kΩ)
Decoding	Live view / Playback resolution: 8MP / 6MP / 5MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF Capability: 8-ch@1080P

Product Details

Hikvision DS-7716NI-K4 provides these key features:

- Third-party network cameras supported
- Up to 8 Megapixels resolution recording
- Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution
- 16/32-ch network cameras can be connected with 160M/256M incoming bandwidth
- Up to 4 SATA interfaces
- Support dual-os to ensure high reliability of system running
- Support various VCA detection alarm and VCA search
- Support H.265/H.264/MPEG4 video formats

Compare to Similar Item

Table 2 shows the comparison.

Model	DS-7716NI-I4	DS-7716NI-K4
Video/Audio input	IP video input: 16-ch, Up to 12 MP resolution Two-way audio: 1-ch, RCA (2.0 Vp-p, 1kΩ)	IP video input: 16-ch Two-way audio: 1-ch, RCA (2.0 Vp-p, 1kΩ)
Network	Incoming bandwidth: 160 Mbps Outgoing bandwidth: 256 Mbps Remote connection: 128	Incoming bandwidth: 160 Mbps Outgoing bandwidth: 160 Mbps Remote connection: 128

Video/Audio output	Recording resolution: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF HDMI output resolution: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA output resolution: 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz Audio output: 1-ch, RCA (Linear, 1 KΩ)	Recording resolution: 8MP / 6MP / 5MP / 4MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF HDMI output resolution: 1-ch, resolution: 4K (3840*2160)/60Hz, 4K (3840*2160)/30Hz, 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz VGA output resolution: 1-ch, resolution: 1920*1080P/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz Audio output: 1-ch, RCA (Linear, 1kΩ)
Decoding	Decoding format: H.265/H.264/MPEG4 Live view / Playback resolution: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF Synchronous playback: 16-ch Capability: 4-ch @ 4K, or 16-ch @ 1080p	Live view / Playback resolution: 8MP / 6MP / 5MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF Capability: 8-ch@1080P

Get More Information

Do you have any question about the DS-7716NI-K4?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

DS-7716NI-K4 Specification	
Video/Audio input	IP video input: 16-ch Two-way audio: 1-ch, RCA (2.0 Vp-p, 1kΩ)
Network	Incoming bandwidth: 160 Mbps Outgoing bandwidth: 160 Mbps Remote connection: 128
Video/Audio output	Recording resolution: 8MP / 6MP / 5MP / 4MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF HDMI output resolution: 1-ch, resolution: 4K (3840*2160)/60Hz, 4K (3840*2160)/30Hz, 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz VGA output resolution: 1-ch, resolution: 1920*1080P/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz Audio output: 1-ch, RCA (Linear, 1kΩ)
Decoding	Live view / Playback resolution: 8MP / 6MP / 5MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF Capability: 8-ch@1080P
Hard disk	SATA: 4 SATA interfaces for 4HDDs Capacity: Up to 6TB capacity for each HDD
External interface	Network interface: 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces Serial interface: RS-232; RS-485; USB interface: Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0 Alarm in/out: 16/4
General	Power supply: 100 to 240 VAC Power: ≤20 W Consumption (without hard disk): ≤20 W Working temperature: -10 to +55°C (14 to 131°F) Working humidity: 10 to 90 % Chassis: 19-inch rack-mounted 1.5U chassis Dimensions (W × D × H): 445 × 390 ×70 mm (17.5"× 15.3" × 2.8")

Contact Us

Want to buy this series of products? please contact us:

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com

Order Now

GO to buy this product: <https://www.router-switch.com/ds-7716ni-k4.html>