

## Product data sheet

**HLD1122D41M8**

### Characteristics

**Monolithic pilot light, HLD11, 220 V AC, half cover head, short terminal, capacitance type, blue**



#### Main

Range of product	HLD11
Device presentation	Monolithic product
Product or component type	Pilot light
Head type	Half-cover head
Load type	Capacitive
Bezel material	Plastic
Mounting diameter	22 mm

#### Complementary

[Us] rated supply voltage	220 V AC
Shape of signaling unit head	Round
Shape	Short
Cap/operator or lens colour	Blue
Connections - terminals	Screw clamp terminals
Service life in hours	30000 h
E-commerce address	Hld11

#### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP65

## Product data sheet

## HLD1122D41M4

### Characteristics

Monolithic pilot light, HLD11, 220 V AC, half cover head, short terminal, capacitance type, red



### Main

Range of product	HLD11
Device presentation	Monolithic product
Product or component type	Pilot light
Head type	Half-cover head
Load type	Capacitive
Bezel material	Plastic
Mounting diameter	22 mm

### Complementary

[Us] rated supply voltage	220 V AC
Shape of signaling unit head	Round
Shape	Short
Cap/operator or lens colour	Red
Connections - terminals	Screw clamp terminals
Service life in hours	30000 h
E-commerce address	Hld11

### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP65

## Product data sheet

## HLD1122D41M5

### Characteristics

Monolithic pilot light, HLD11, 220 V AC, half cover head, short terminal, capacitance type, yellow



### Main

Range of product	HLD11
Device presentation	Monolithic product
Product or component type	Pilot light
Head type	Half-cover head
Load type	Capacitive
Bezel material	Plastic
Mounting diameter	22 mm

### Complementary

[Us] rated supply voltage	220 V AC
Shape of signaling unit head	Round
Shape	Short
Cap/operator or lens colour	Yellow
Connections - terminals	Screw clamp terminals
Service life in hours	30000 h
E-commerce address	Hld11

### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP65

**Product data sheet**

**HLD1122D41M3**

**Characteristics**

**Monolithic pilot light, HLD11, 220 V AC, half cover head, short terminal, capacitance type, green**



**Main**

Range of product	HLD11
Device presentation	Monolithic product
Product or component type	Pilot light
Head type	Half-cover head
Load type	Capacitive
Bezel material	Plastic
Mounting diameter	22 mm

**Complementary**

[Us] rated supply voltage	220 V AC
Shape of signaling unit head	Round
Shape	Short
Cap/operator or lens colour	Green
Connections - terminals	Screw clamp terminals
Service life in hours	30000 h
E-commerce address	Hld11

**Environment**

Standards	IEC 60947-5-1
IP degree of protection	IP65