

Product data sheet

HRT1600ZS

Characteristics

Blade fuse, HRT16, fuse size 00, base (resin)



Main

| | |
|---------------------------|------------|
| Range of product | HRT16 |
| Product or component type | Fuse |
| Fuse type | Blade type |
| Device application | Protection |
| Fuse curve | GG |
| Fuse size | 00 |

Complementary

| | |
|--------------------------------|--------------|
| [Ue] rated operational voltage | 500/690 V AC |
|--------------------------------|--------------|

Environment

| | |
|---------------------------------------|------------|
| Standards | EN 60269 |
| Product certifications | CE |
| Ambient air temperature for operation | -5...40 °C |
| Operating altitude | |

Product data sheet

HRT161ZS

Characteristics

Blade fuse, HRT16, fuse size 1, 250 A, base resin



Main

| | |
|---------------------------|------------|
| Range of product | HRT16 |
| Product or component type | Fuse |
| Fuse type | Blade type |
| Device application | Protection |
| Fuse curve | GG |
| Fuse size | 1 |

Complementary

| | |
|--------------------------------|--------------|
| [Ue] rated operational voltage | 500/690 V AC |
| [In] rated current | 250 A |

Environment

| | |
|---------------------------------------|------------|
| Standards | EN 60269 |
| Product certifications | CE |
| Ambient air temperature for operation | -5...40 °C |
| Operating altitude | |

Product data sheet

HRT162ZS

Characteristics

Blade fuse, HRT16, fuse size 2, 400 A, base resin



Main

| | |
|---------------------------|------------|
| Range of product | HRT16 |
| Product or component type | Fuse |
| Fuse type | Blade type |
| Device application | Protection |
| Fuse curve | GG |
| Fuse size | 2 |

Complementary

| | |
|--------------------------------|--------------|
| [Ue] rated operational voltage | 500/690 V AC |
| [In] rated current | 400 A |

Environment

| | |
|---------------------------------------|------------|
| Standards | EN 60269 |
| Product certifications | CE |
| Ambient air temperature for operation | -5...40 °C |
| Operating altitude | |

Product data sheet

HRT163ZS

Characteristics

Blade fuse, HRT16, fuse size 3, 630 A, base resin



Main

| | |
|---------------------------|------------|
| Range of product | HRT16 |
| Product or component type | Fuse |
| Fuse type | Blade type |
| Device application | Protection |
| Fuse curve | GG |
| Fuse size | 3 |

Complementary

| | |
|--------------------------------|--------------|
| [Ue] rated operational voltage | 500/690 V AC |
| [In] rated current | 630 A |

Environment

| | |
|---------------------------------------|------------|
| Standards | EN 60269 |
| Product certifications | CE |
| Ambient air temperature for operation | -5...40 °C |
| Operating altitude | |