

Product sheet



ELOE LEGRAND

Eloe - 1 gang single TV socket - female type - White

REF. 618027 | EAN. 3414972265331

[> Visit e-catalogue](#)

Product characteristics

- Check diametre
- ELOE is sold as a complete set under one cat number
- LTE protected class A level
- Attenuation loss < 1,5 dB
- Glossy white finish

Recommendations / Restrictions

- Looping connection unadapted. Recommended inside use only

The product's benefits

Installation

- Visual check of the connection. Secured screw connection.

Usage

- Limited cable bend radius that lower attenuation losses

Advantages

- Low attenuation socket
- Fully protected against EMC perturbances (=3G, 4G, 5G... risk of image pixelation)
- A squarish shape designed with a full rocker plate aesthetic

Technical characteristics

| | |
|--|-------------------------------------|
| Model | End socket |
| Type of socket outlet | TV |
| DAB+ | No |
| Mounting method | Flush-mounted |
| Number of modules (module system) | 1 |
| Assembly arrangement | Basic element with full cover plate |

| | |
|---------------------------------------|---------------|
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Antimicrobial treatment | No |
| Degree of protection (IP) | IP20 |
| degree of impact strength (IK) | IK04 |
| Device width | 86 mm |

| | |
|-------------------------|---------------------|
| Number of outlets | 1 |
| Through loss at 860 MHz | 1 dB |
| Type of fastening | Mounting with screw |
| Colour | White |
| RAL-number (similar) | 9003 |
| Surface protection | Untreated |
| Surface finishing | Glossy |

| | |
|---|-----------|
| Device height | 86 mm |
| Device depth | 28.3 mm |
| Min. depth of built-in installation box | 18.8 mm |
| Operating / setting temperature (Min-Max) | -5-50 °C |
| Storage temperature (Min-Max) | -10-70 °C |

Documentation

TECHNICAL DOCUMENTATION



LE09196AA.pdf | PDF (0.48Mo)



F03768EN-00.pdf | PDF (0.52Mo)

CATALOGUE PAGE & OTHERS



ex223001_0663.pdf | PDF (0.07Mo)