

# Product sheet



OBRIA LEGRAND

Obria 1 gang 2W 16Ax Switch - Matt White

REF. MEC22002WH | EAN. 3414972668408

Allows to control two points of lighting.

> [Visit e-catalogue](#)

## Description

Allows to control two points of lighting.

### Product characteristics

- Sold as a complete set under one cat number
- 16AX, 250V
- Screw type terminals for enhanced contacts and open terminal for easy to install
- Matt White Finish

### Recommendations / Restrictions

- Recommended inside use only

## The product's benefits

### Installation

- Quick and Easy plate-rocker clipping system

### Usage

- Practical 1-point lighting control on a single plate

### Advantages

- Technicity and Robustness of the support frame
- Modern full plate design for a perfect decoration integration

## Technical characteristics

Wiring system	Two-way switch
Method of operation	Rocker/button
Assembly arrangement	Basic element with housing top
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic

Monitoring contact	No
Connection type	Screwed terminal
Heating switch	No
Washing machine switch	No
Device width	86 mm
Device height	87.4 mm
Device depth	39.1 mm
Built-in depth	24.4 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No

Material quality	Thermoplastic
Halogen free	No
Antimicrobial treatment	No
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9003
Colour of switch operator	White
Label space/information surface	No
Lighting	No
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Nominal voltage	250 V
Rated current	16 A
Switching current for fluorescent lamps	16 AX

Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Compliant with UK Building Regulations Part M	No
Operating / setting temperature (Min-Max)	-5-35 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Mandatory neutral	No
Terminal marking indication	Yes
Terminals capacity (Min-Max)	1-4 mm <sup>2</sup>
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	1-4 mm <sup>2</sup>
Tube diameter for wall mounted product (Min-Max)	16-32 mm

## Documentation

### TECHNICAL DOCUMENTATION



F04211EN-00.pdf | PDF (0.53Mo)

### Agreements & Certificates



OC / CB-CNCVC1666 | (0.65Mo)