

# Product sheet



## OBRIA LEGRAND

### Obria 1 gang 2W 16Ax Switch - Dark Silver

REF. MEC22002SL | EAN. 3414972668378

Allows to control two points of lighting.

> [Visit e-catalogue](#)

## Description

Allows to control two points of lighting.

### Product characteristics

- Sold as a complete set under one cat number
- 16AX, 250V
- Screw type terminals for enhanced contacts and open terminal for easy to install
- Dark Silver Finish

### Recommendations / Restrictions

- Recommended inside use only

## Technical characteristics

## The product's benefits

### Installation

- Quick and Easy plate-rocker clipping system

### Usage

- Practical 1-point lighting control on a single plate

### Advantages

- Technicity and Robustness of the support frame
- Modern full plate design for a perfect decoration integration

<b>Wiring system</b>	Two-way switch
<b>Method of operation</b>	Rocker/button
<b>Assembly arrangement</b>	Basic element with housing top
<b>Push button switch</b>	No
<b>Number of rockers</b>	1
<b>Mounting method</b>	Flush-mounted
<b>Type of fastening</b>	Screw mounting
<b>With mounting plate</b>	No
<b>Material</b>	Plastic

<b>Connection type</b>	Screwed terminal
<b>Heating switch</b>	No
<b>Washing machine switch</b>	No
<b>Device width</b>	86 mm
<b>Device height</b>	87.4 mm
<b>Device depth</b>	39.1 mm
<b>Built-in depth</b>	24.4 mm
<b>Min. depth of built-in installation box</b>	35 mm
<b>Compatible with Apple HomeKit</b>	No
<b>Compatible with Google Assistant</b>	No

Material quality	Thermoplastic
Halogen free	No
Antimicrobial treatment	No
Surface protection	Lacquered
Surface finishing	Matt
Colour	Silver
Colour of switch operator	Silver
Label space/information surface	No
Lighting	No
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Nominal voltage	250 V
Rated current	16 A
Switching current for fluorescent lamps	16 AX
Monitoring contact	No

Compatible with Amazon Alexa	No
IFTTT support available	No
Compliant with UK Building Regulations Part M	No
Operating / setting temperature (Min-Max)	-5-35 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Mandatory neutral	No
Terminal marking indication	Yes
Terminals capacity (Min-Max)	1-4 mm <sup>2</sup>
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	1-4 mm <sup>2</sup>
Tube diameter for wall mounted product (Min-Max)	16-32 mm

## Documentation

### TECHNICAL DOCUMENTATION



F04211EN-00.pdf | PDF (0.53Mo)

### Agreements & Certificates



OC / CB-CNCVC1666 | (0.65Mo)