

Type		UA-1	UA-2, 4	AU-100
Rated operation voltage (Ue)			600V	600V
Rated insulation voltage (Ui)			1000V	690V
Rated impulse withstand voltage (Uimp)			8kV	6kV
Rated frequency			50/60Hz	50/60Hz
Contact sensibility	Voltage		DC 24V	DC 24V
	Current		DC 10mA	DC 10mA
Rated thermal current (Ith, AC12 duty)			16A	16A
Rated operation current				
AC15 duty	120V		6A	6A
	240V		3A	3A
	380V		1.9A	1.9A
	480V		1.5A	1.5A
	500V		1.4A	1.4A
	600V		1.2A	1.2A
DC13 duty	125V		1.1A	1.1A
	250V		0.55A	0.55A
	400V		0.31A	0.31A
	500V		0.27A	0.27A
	600V		0.2A	0.2A
			0.1A	
Rated Short-time withstand current	1s		100A	-
	0.5s		125A	-
	0.1s		145A	-
Electrical lifetime (mil. operations)				
AC15 duty	220V		0.25	0.25
	440V		0.25	0.25
DC13 duty	220V		0.25	0.25
	440V		0.25	0.25
Maximum operating cycles per hour			1800	1800
Conductor size (Solid, stranded)		AWG	18-10	18-10
(the max. number of conducts : 2)		mm2	1-2.5	1-2.5