

3 POLE MCB					
ITEM CODE	RATED CURRENT	NO.POLES	TYPE	RATED VOLTAGE	RATED SHORT CIRCUIT CAPACITY (Icn)
470-3020	6A	3	C	400V	6kA
470-3021	10A	3	C	400V	6kA
470-3022	16A	3	C	400V	6kA
470-3023	20A	3	C	400V	6kA
470-3025	32A	3	C	400V	6kA
470-3026	40A	3	C	400V	6kA
470-3028	63A	3	C	400V	6kA

## APPLICATIONS

Industrial/Residential/Hotel/General Purpose

## PRODUCT SPECIFICATIONS

Connection	: Screw type terminals
Method of Installation	: Mounting on 35mm DIN rail
Warranty Period	: Lifetime warranty*
Standard Complied	: IEC 60898-1 / SLS 1175
Certification	: SLS
Protection	: Against overload and short circuit
Protected Poles	: All poles protected
Rated Voltage	: 3 pole - 400VAC
Rated Frequency	: 50/60Hz
Rated Current	: 6, 10, 16, 20, 32, 40, 63 A
Type of Trip	: Thermal/ Magnetic release
Rated Service Short Circuit Capacity(Ics)	: 6kA
Temperature Limit	: -5 °C to +40 °C
Instantaneous Tripping Characteristics	: Type C
Degree of Protection	: IP20
Rated Impulse withstand Voltage(Uimp)	: 4kV

