

4 POLE MCB					
ITEM CODE	RATED CURRENT	NO.POLES	TYPE	RATED VOLTAGE	RATED SHORT CIRCUIT CAPACITY (Icn)
470-3029	6A	4	C	400V	6kA
470-3030	10A	4	C	400V	6kA
470-3031	16A	4	C	400V	6kA
470-3032	20A	4	C	400V	6kA
470-3034	32A	4	C	400V	6kA
470-3035	40A	4	C	400V	6kA
470-3037	63A	4	C	400V	6kA

APPLICATIONS

Industrial/Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

Connection	: Screw type terminals
Method of Installation	: Mounting on 35mm DIN rail
Warranty Period	: Lifetime warranty*
Standard Complied	: IEC 60898-1 / SLS 1175
Certification	: SLS
Protection	: Against overload and short circuit
Protected Poles	: All poles protected
Rated Voltage	: 4 pole - 400VAC
Rated Frequency	: 50/60Hz
Rated Current	: 6, 10, 16, 20, 32, 40, 63 A
Type of Trip	: Thermal/Magnetic release
Rated Service Short Circuit Capacity(Ics)	: 6kA
Temperature Limit	: -5 °C to +40 °C
Instantaneous Tripping Characteristics	: Type C
Degree of Protection	: IP20
Rated Impulse Withstand Voltage(Uimp)	: 4kV

