

3P + N RCCB				
ITEM CODE	RATED CURRENT	NO.POLES	RATED VOLTAGE	RATED RESIDUAL OPERATING CURRENT
471-4007	40A	3P+N	400V	30mA
471-4008	40A	3P+N	400V	100mA
471-4010	63A	3P+N	400V	30mA
471-4011	63A	3P+N	400V	100mA
471-4012	63A	3P+N	400V	300mA

APPLICATIONS

Industrial/Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

Connection	: Screw type terminals
Method of Installation	: Mounting on 35mm DIN rail
Warranty Period	: Lifetime warranty*
Standard Complied	: IEC 61008-1 & IEC 61008-2-1
Certification	: CB, KEMA
Rated Voltage (Un)	: 400VAC (3P + N)
Rated Frequency	: 50Hz
Rated Current (In)	: 40, 63A
Time Delay	: Without time delay
Rated Residual Current (IΔn)	: 30, 100mA for 40A & 30, 100, 300mA for 63A
Rated Conditional Short Circuit Current (Inc)	: 10kA
Rated Conditional Residual Short Circuit Current (IΔc)	: 10kA
Rated Making and Breaking Capacity (Im)	: 500A or 10 In whichever is greater
Rated Residual Making and Breaking Capacity (IΔm)	: 500A or 10 In whichever is greater
Operating Characteristic in Presence of Residual Current with d.c Components	: Type AC
Ambient Temperature Limit	: -25 °C to +40 °C



OVER LOAD & SHORT CIRCUIT PROTECTION DEVICES FOR RCCB

RCCB Rating (A)	MCB Rating			
	32A	40A	63A	100A
40	✓	✓		
63			✓	
100				✓

