



SE300

Tachometers/Tacho meter



Basic Features

- Designed for ease of holding to enable stable measurement
- Max/Min value hold
- Auto power off (2min.) (cancelable)
- Fixed installation possible using a commercially available camera tripod
- Contact measurement (optional ENC-3)

Optional Accessories

Reflective sticker (50stickersX2sheets) : SE-T3
Contact measurement attachment : ENC-3
(contact adapter, contact marker and rim speed ring)
contact marker : SE-A30
Rim speed ring : SE-A31

Specifications

**DATA
HOLD****AP
OFF****MAX
MIN
AVG****BACK
LIGHT**

SE300	Non-contact	Contact (optional ENC-3)	Best accuracy
rpm	30,0~99999	30,0~19999	±(0.03%+1)
rps	0.50~1600.0	0.50~333.00	
ms	0,600~1999,0	3,000~1999,0	
count	0~99999	0~99999	
m/min	-	3,0~1999,0	
m/s	-	0.05~33.00	
Detection distance	Approx. 50~500mm		
Battery	R6P/LR6X2		
Size / Mass	H210XW60XD55mm/approx. 218g		
Standard	Reflective sticker(SE-T3), Carrying case(C-SE300),		
accessories included	Instruction manual		

Copyright © 2012 Sanwa Electric Instrument Co., Ltd. All Rights Reserved.