



Main

Range of product	Acti 9
Product or component type	Undervoltage release
Device short name	IMN
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

Complementary

Range compatibility	Acti 9: Acti 9 iDPN (China version) Acti 9: Acti 9 iDPN Vigi Acti 9: Acti 9 iC40 Acti 9: Acti 9 iC65 Acti 9: Acti 9 ARA Acti 9: Acti 9 iID Acti 9: Acti 9 iSW-NA Acti 9: Acti 9 RCA Acti 9: Acti 9 iC60 (double terminals miniature circuit breaker)
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 8 mm ² rigid Clamp terminal 2 cable(s) 2.7 mm ² rigid Clamp terminal 1 cable(s) 6 mm ² flexible

Clamp terminal 2 cable(s) 2.7 mm² flexible with cable end cable end

Tightening torque

1 N.m

Environment

Standards

EN/IEC 60947-5-1

Tropicalisation

2 conforming to EN/IEC 60947-5-1

Relative humidity

95 % at 55 °C

Ambient air temperature for operation

-25...50 °C

Ambient air temperature for storage

-40...85 °C

Offer Sustainability

Sustainable offer status

Green Premium product

RoHS (date code: YYWW)

Compliant - since 1216 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH

Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Product environmental profile

Available

Product end of life instructions

Available

Contractual warranty

Warranty period

18 months