

# Product datasheet

Specifications



## TeSys LRD thermal overload relays - 0.16...0.25 A - class 10A

LRD02

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Product Name</b>	TeSys LRD TeSys Deca
<b>Product Or Component Type</b>	Differential thermal overload relay
<b>Device Short Name</b>	LRD
<b>Relay Application</b>	Motor protection
<b>Product Compatibility</b>	LC1D25 LC1D38 LC1D12 LC1D09 LC1D18 LC1D32
<b>Network Type</b>	DC AC
<b>Thermal Overload Class</b>	Class 10A conforming to IEC 60947-4-1
<b>Thermal Protection Adjustment Range</b>	0.16...0.25 A
<b>[Ui] Rated Insulation Voltage</b>	Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL Power circuit: 690 V conforming to IEC 60947-4-1

### Complementary

<b>Network Frequency</b>	0...400 Hz
<b>Mounting Support</b>	Plate, with specific accessories Rail, with specific accessories Under contactor
<b>Tripping Threshold</b>	1.14 +/- 0.06 I <sub>r</sub> conforming to IEC 60947-4-1
<b>Auxiliary Contact Composition</b>	1 NO + 1 NC
<b>[I<sub>th</sub>] Conventional Free Air Thermal Current</b>	5 A for signalling circuit
<b>Permissible Current</b>	3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit
<b>[U<sub>e</sub>] Rated Operational Voltage</b>	690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1
<b>Associated Fuse Rating</b>	4 A gG for signalling circuit 4 A BS for signalling circuit
<b>[U<sub>imp</sub>] Rated Impulse Withstand Voltage</b>	6 kV
<b>Phase Failure Sensitivity</b>	Tripping current 130 % of I <sub>r</sub> on two phase, the last one at 0
<b>Control Type</b>	Red push-button: stop Blue push-button: reset

<b>Temperature Compensation</b>	-20...60 °C
<b>Connections - Terminals</b>	Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 1...6 mm <sup>2</sup> solid without cable end
<b>Tightening Torque</b>	Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 1.7 N.m - on screw clamp terminals
<b>Height</b>	66 mm
<b>Width</b>	45 mm
<b>Depth</b>	70 mm
<b>Net Weight</b>	0.124 kg

## Environment

<b>Climatic Withstand</b>	conforming to IACS E10
<b>Ip Degree Of Protection</b>	IP20 conforming to IEC 60529
<b>Ambient Air Temperature For Operation</b>	-20...60 °C without derating conforming to IEC 60947-4-1
<b>Ambient Air Temperature For Storage</b>	-60...70 °C
<b>Flame Retardance</b>	V1 conforming to UL 94
<b>Mechanical Robustness</b>	Vibrations: 6 Gn conforming to IEC 60068-2-6 Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7
<b>Dielectric Strength</b>	1.89 kV at 50 Hz conforming to IEC 60947-1
<b>Standards</b>	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495
<b>Product Certifications</b>	IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	5.000 cm
<b>Package 1 Width</b>	8.000 cm
<b>Package 1 Length</b>	9.000 cm
<b>Package 1 Weight</b>	136.000 g
<b>Unit Type Of Package 2</b>	S02

<b>Number Of Units In Package 2</b>	24
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	3.576 kg
<b>Unit Type Of Package 3</b>	P06
<b>Number Of Units In Package 3</b>	384
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	65.328 kg

## Contractual warranty

<b>Warranty</b>	12 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)