

| TECHNICAL SPECIFICATION        |   |                         |                         |                         |
|--------------------------------|---|-------------------------|-------------------------|-------------------------|
| POWER                          |   | 1250VA                  | 1500VA                  | 2000VA                  |
| BACKUP OPTIONS                 | I   | 2-PC (With 15" Monitor) | 3-PC (With 15" Monitor) | 4-PC (With 15" Monitor) |
|                                | II  | 1PC +1 FAN + 1 SAVER    | 1PC +2 FAN + 2 SAVER    | 2PC +2 FAN + 2 SAVER    |
|                                | III   | 4 FAN + 4 SAVER         | 6 FAN + 6 SAVER         | 8 FAN + 8 SAVER         |
| NOMINAL INPUT                  | 220 VAC, SINGLE PHASE   |                         |                         |                         |
| AVR (BATTERY CHARGING MODE)    | BATTERY CHARGING UP TO 150V MAINS INPUT   |                         |                         |                         |
| VOLTAGE (ONBACK-UP)            | 220 VAC, (REGULATED)  |                         |                         |                         |
| INPUT FILTERING                | EMI / RFI FILTERS AND MOV SURGE SUPPRESSOR  |                         |                         |                         |
| WAVEFORM                       | STEP SINE   |                         |                         |                         |
| FREQUENCY                      | 50 Hz   |                         |                         |                         |
| TRANSFER TIME                  | 4-6 ms  |                         |                         |                         |
| OVER LOAD PROTECTION           | ELECTRONIC OVER LOAD & FUSE   |                         |                         |                         |
| BATTERY TYPE                   | SULFURIC ACID (WET) OR SEALED LEAD ACID (DRY) BATTERY                             |                         |                         |                         |
| BATTERY RATING                 | 12V/150-200 AH x 1  | 12V/100-150 AH x 2      | 12V/150-200 AH x 2      |                         |
| BACKUP TIME                    | 2 - 2½ Hrs  | 2 - 3 Hrs               | 2 - 3 Hrs               |                         |
| BATTERY DISCHARGING MANAGEMENT | BATTERY LOW INDICATION + BEEP AND AUTOMATIC SHUTDOWN                              |                         |                         |                         |
| BATTERY PROTECTION             | DEEP DISCHARGE AND OVER CHARGING  |                         |                         |                         |
| RECHARGE TIME                  | 2-3 Hrs AT 150 - 240 VAC  |                         |                         |                         |
| FRONT PANEL INDICATIONS        | MAINS, BATTERY CHARGING, FULL BATTERY, INVERTOR (FLASHING) OVER LOAD, LOW BATTERY |                         |                         |                         |
| AUDIBLE ALARM                  | AT LOW BATTERY  |                         |                         |                         |
| AUDIBLE NOISE                  | < 45 dB (1-METER FROM SURFACE)  |                         |                         |                         |
| WARRANTY                       | ONE YEAR (WITHOUT BATTERY)  |                         |                         |                         |

**Note: Design and specifications subject to change without any prior notice.**

DEALER

