

TECHNICAL SPECIFICATION				
POWER		1250VA	1500VA	2000VA
BACKUP OPTIONS	I	2-PC (With 15" Monitor)	3-PC (With 15" Monitor)	4-PC (With 15" Monitor)
	II	1PC +1 FAN + 1 SAVER	1PC +2 FAN + 2 SAVER	2PC +2 FAN + 2 SAVER
	III	4 FAN + 4 SAVER	6 FAN + 6 SAVER	8 FAN + 8 SAVER
NOMINAL INPUT	220 VAC, SINGLE PHASE			
AVR (BATTERY CHARGING MODE)	BATTERY CHARGING UP TO 150V MAINS INPUT			
VOLTAGE (ONBACK-UP)	220 VAC, (REGULATED)			
INPUT FILTERING	EMI / RFI FILTERS AND MOV SURGE SUPPRESSOR			
WAVEFORM	STEP SINE			
FREQUENCY	50 Hz			
TRANSFER TIME	4-6 ms			
OVER LOAD PROTECTION	ELECTRONIC OVER LOAD & FUSE			
BATTERY TYPE	SULFURIC ACID (WET) OR SEALED LEAD ACID (DRY) BATTERY			
BATTERY RATING	12V/150-200 AH x 1	12V/100-150 AH x 2	12V/150-200 AH x 2	
BACKUP TIME	2 - 2½ Hrs	2 - 3 Hrs	2 - 3 Hrs	
BATTERY DISCHARGING MANAGEMENT	BATTERY LOW INDICATION + BEEP AND AUTOMATIC SHUTDOWN			
BATTERY PROTECTION	DEEP DISCHARGE AND OVER CHARGING			
RECHARGE TIME	2-3 Hrs AT 150 - 240 VAC			
FRONT PANEL INDICATIONS	MAINS, BATTERY CHARGING, FULL BATTERY, INVERTOR (FLASHING) OVER LOAD, LOW BATTERY			
AUDIBLE ALARM	AT LOW BATTERY			
AUDIBLE NOISE	< 45 dB (1-METER FROM SURFACE)			
WARRANTY	ONE YEAR (WITHOUT BATTERY)			

Note: Design and specifications subject to change without any prior notice.

DEALER

