

| TECHNICAL SPECIFICATION | | | | |
|--------------------------------|---|-------------------------|-------------------------|-------------------------|
| POWER | | 1250VA | 1500VA | 2000VA |
| BACKUP OPTIONS | I | 2-PC (With 15" Monitor) | 3-PC (With 15" Monitor) | 4-PC (With 15" Monitor) |
| | II | 1PC +1 FAN + 1 SAVER | 1PC +2 FAN + 2 SAVER | 2PC +2 FAN + 2 SAVER |
| | III | 4 FAN + 4 SAVER | 6 FAN + 6 SAVER | 8 FAN + 8 SAVER |
| NOMINAL INPUT | 220 VAC, SINGLE PHASE | | | |
| AVR (BATTERY CHARGING MODE) | BATTERY CHARGING UP TO 150V MAINS INPUT | | | |
| VOLTAGE (ONBACK-UP) | 220 VAC, (REGULATED) | | | |
| INPUT FILTERING | EMI / RFI FILTERS AND MOV SURGE SUPPRESSOR | | | |
| WAVEFORM | STEP SINE | | | |
| FREQUENCY | 50 Hz | | | |
| TRANSFER TIME | 4-6 ms | | | |
| OVER LOAD PROTECTION | ELECTRONIC OVER LOAD & FUSE | | | |
| BATTERY TYPE | SULFURIC ACID (WET) OR SEALED LEAD ACID (DRY) BATTERY | | | |
| BATTERY RATING | 12V/150-200 AH x 1 | 12V/100-150 AH x 2 | 12V/150-200 AH x 2 | |
| BACKUP TIME | 2 - 2½ Hrs | 2 - 3 Hrs | 2 - 3 Hrs | |
| BATTERY DISCHARGING MANAGEMENT | BATTERY LOW INDICATION + BEEP AND AUTOMATIC SHUTDOWN | | | |
| BATTERY PROTECTION | DEEP DISCHARGE AND OVER CHARGING | | | |
| RECHARGE TIME | 2-3 Hrs AT 150 - 240 VAC | | | |
| FRONT PANEL INDICATIONS | MAINS, BATTERY CHARGING, FULL BATTERY, INVERTOR (FLASHING) OVER LOAD, LOW BATTERY | | | |
| AUDIBLE ALARM | AT LOW BATTERY | | | |
| AUDIBLE NOISE | < 45 dB (1-METER FROM SURFACE) | | | |
| WARRANTY | ONE YEAR (WITHOUT BATTERY) | | | |

Note: Design and specifications subject to change without any prior notice.

DEALER

