

SQUARE SURFACE DOWNLIGHT





Features

- Its clean and classic design makes it easy to fix and maintain for a wide range of application.
- Its surface mounted frame works as an individual fitting of surface downlight.
- Ideal for surfaces where false ceiling is not available.
- Provides good heat dissipation with built-in Aluminium profile and thermal conductive plastic housing that ensures safety.
- Working temperature: -20°C ~ 40°C.
- Available in 3000K, 4000K, 6500K color temperature options.
- Rated life 50,000hours.

Specifications

Coarts Square Surface Downlight offers a clean and classic design that transforms ambient lighting into an exquisite balance of refined appearance and superior efficiency. It is a perfect choice for retrofitting or updating existing surface mount fixtures.

Applications

- · General Lighting of offices
- Retail outlets
- Healthcare facilities
- Education institutes
- Industries

PRODUCT CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (Im) 3000K / 4000K / 6500K	DIMENSIONS (mm)
CLS-SQ-SMDL-12W	12	85-265 VAC	>0.5	3000K / 4000K / 6500K	840 / 880 / 925	160 X 160 X 28
CLS-SQ-SMDL-18W	18				1260 / 1320 / 1390	210 X 210 X 28
CLS-SQ-SMDL-24W	24				1680 / 1760 / 1850	285 X 285 X 28

