



LED WALL LIGHT  
**TONE ECO**



ARCHITECTURAL LIGHT

SURFACE

AC 220-240V

120°

CRI≥80

NON DIMMABLE

3 IN 1  
SLIDE SWITCH  
3 CCT  
3000K/4000K/6500K

PF≥0.9

IP65

RoHS

CE

LIFE 50000 HOURS

**FEATURES**

- Smooth GRP moisture-proof housing.
- PC diffuser.
- AC200-240V integral LED driver.
- Highly efficient more than 100lm/W SMD 2835 LED chip.
- 3CCT selectable switch for 3000K, 4000K and 6000K CCT options.
- Ceiling/wall mounting options with installation brackets.
- Protection rating IP65 / IK06.
- Operating temperature -10°C to 45°C.
- CE, RoHS complied

**APPLICATIONS**

- Corridors
- Boundary walls
- Patio
- Pool sites
- Roof terraces


**SPECIFICATIONS**

CODE	WATTS (W)	CCT (K)	LUMENS (lm)* 3000K / 4000K / 6500K	DIMENSIONS (mm) A X B X C
TONEECO-20W	20	3000K / 4000K / 6500K	1900 / 2050 / 2130	276 X 146 X 76

\*Lumen output with ±10% tolerance.



**DIMENSIONS**



**PHOTOMETRICS**

