



UT136C+



Specifications	Range	UT136B+	UT136C+
DC voltage (V)	1000V	$\pm(0.7\%+3)$	$\pm(0.7\%+3)$
AC voltage (V)	1000V	$\pm(1\%+3)$	$\pm(1\%+3)$
DC current (A)	10A	$\pm(1\%+3)$	$\pm(1\%+3)$
AC current (A)	10A	$\pm(1.2\%+5)$	$\pm(1.2\%+5)$
Resistance (Ω)	40M Ω	$\pm(0.8\%+2)$	$\pm(0.8\%+2)$
Capacitance (F)	40mF	$\pm(3\%+5)$	$\pm(3\%+5)$
Frequency (Hz)	400Hz~40MHz	$\pm(0.1\%+4)$	$\pm(0.1\%+4)$
Temperature ($^{\circ}\text{C}$)	-40~1000 $^{\circ}\text{C}$		$\pm(1\%+3)$
Temperature ($^{\circ}\text{F}$)	-40~1832 $^{\circ}\text{F}$		$\pm(1.5\%+5)$
Display count		4000	4000
NCV		v	
Category ratings	CAT II 1000V, CAT III 600V		

Features

Equipped with 3mm protective sleeve	Measures up to 1000V and 10A AC/DC current
Quick sampling rate, up to 4 times/s	Large LCD display
Transistor measurement	Quick capacitor measurement (measures 1mF in 4 seconds)
Overload alarm	Diode/continuity buzzer
LCD backlight	Data hold/Auto power off
2m drop proof	Low power consumption and auto power saving function

Characteristics

Standard accessories	Batteries, test leads, temperature probe (UT136C+), English manual
Power	1.5V battery (R6) x 2
Display	56.5 x 36mm
Product size	175 x 83 x 53mm
Product net weight	330g
Standard individual packing	Gift Box
Standard quantity per carton	30pcs
Standard carton measurement	390 x 355 x 355mm
Standard carton gross weight	14.8kg