



■ UT216A



■ UT216B

### SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT216A	UT216B
AC Current(A)	6A/60A/600A 60A/600A (50~400Hz)	±(2.5%+5)	±(2.5%+5)
AC Voltage(V)	6V/60V/600V/750V	±(1.2%+5)	±(1.2%+5)
DC Voltage(V)	600mV/6V/60V/600V/1000V	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1%+2)	±(1%+2)
Capacitance (F)	99.99nF/999.9nF/9.999μF/99.99μF/ 999.9μF/9.999mF/59.99mF	±(4.0%+5)	±(4.0%+5)
Frequency (Hz)	10Hz-1MHz		±(0.1%+4)
Features			
Display Count		6000	6000
Auto Range		√	√
Jaw Capacity		30mm	30mm
True RMS		√	√
Diode	Around 3.0V	√	√
V.F.C.			√
NCV		√	√
Data Hold		√	√
Relative Mode		√	√
MAX/MIN		√	√
LCD Backlight		√	√
Flashlight		√	√
Auto Power Off	Around 15 Minutes	√	√
Continuity Buzzer		√	√
Low Battery Indication	≤3.6V	√	√
Input Protection		√	√
Input Impedance for DCV	≥10MΩ	√	√

### GENERAL CHARACTERISTICS

Power	AAA 1.5V × 3
LCD Size	38mm × 24 mm
Product Color	Red and Grey
Product Net Weight	<b>UT216A</b> - 280g <b>UT216B</b> - 231.7g
Product Size	220mm × 75mm × 40mm
Standard Accessories	Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	485mm × 320mm × 385mm (0.065 CBM Per Standard Carton)
Standard Carton Gross Weight	<b>UT216A</b> - 19.8 kg <b>UT216B</b> - 18 kg